



Medium

## BESTGIRL S3

Classic, low-cut safety shoe with a female touch

Protect and comfort your feet with the Safety Jogger BESTGIRL. Featuring SR slip resistance, steel toecap and midsole, oil & fuel resistance, and S3 safety rating. Ideal for multiple industries.

Upper	Barton Action Leather
Lining	Mesh
Footbed	SJ foam footbed
Midsole	Steel
Outsole	PU/PU
Toecap	Steel
Category	S3 / SRC
Size range	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 JPN 21.5-26.5 / KOR 230-270
Sample weight	0.480 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011



217



**S3**  
S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.

**SRC slip resistance**  
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

**Steel toecap**  
Robust metal support to protect the feet of the wearer against falling or rolling objects.

**Steel midsole**  
Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.

**Oil & fuel resistant**  
The outsole is resistant against oil and fuel.

**Heel energy absorption**  
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

**Industries:**

Automotive, Catering, Chemical, Cleaning, Construction, Food &amp; beverages, Mining, Logistics, Oil &amp; Gas, Industry

**Environments:**

Dry environment, Wet environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
<b>Upper</b>	<b>Barton Action Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	1.6	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	22.9	≥ 15
<b>Lining</b>	<b>Mesh</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	60.5	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	484.1	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
<b>Outsole</b>	<b>PU/PU</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	29.1	≤ 150
	Outsole slip resistance SRA: heel	friction	0.38	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.38	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.16	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.19	≥ 0.18
	Antistatic value	MegaOhm	114.5	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	27	≥ 20
<b>Toecap</b>	<b>Steel</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	15.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	16.5	≥ 14

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.