



Medium

CADOR S3 LOW

CADORS3LOW

Sporty, low-cut ESD safety shoe with a steel toe cap and midsole

This safety shoe is water-resistant, features a steel toe cap, ESD properties, and an SR slip-resistant outsole. The removable foam footbed and Airblaze technology ensure you stay fresh and fit throughout the day in this low-cut model.

| | |
|---------------|---|
| Upper | Synthetic Nubuck |
| Lining | 3D-Mesh |
| Footbed | SJ foam footbed |
| Midsole | Steel |
| Outsole | PU/PU |
| Toecap | Steel |
| Category | S3 / ESD, SRC |
| Size range | EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315 |
| Sample weight | 0.601 kg |
| Norms | ASTM F2413:2018 EN ISO 20345:2011 |



BLK



S3
S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



Steel midsole
Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



Steel toecap
Robust metal support to protect the feet of the wearer against falling or rolling objects.



Airblaze technology
Moisture and temperature management system to provide optimum wearer comfort by keeping your feet dry and comfortable.



Electrostatic Discharge (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

Industries:

Automotive, Assembly, Food & beverages, Industry, Logistics

Environments:

Dry environment, Wet environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20345 |
|----------------|--|-----------------------|-------------|--------------|
| Upper | Synthetic Nubuck | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 2.2 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 28 | ≥ 15 |
| Lining | 3D-Mesh | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 61.1 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 490 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | PU/PU | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 59 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.30 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.39 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.15 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.24 | ≥ 0.18 |
| | Antistatic value | MegaOhm | N/A | 0.1 - 1000 |
| | ESD value | MegaOhm | 79 | 0.1 - 100 |
| | Heel energy absorption | J | 24 | ≥ 20 |
| Toecap | Steel | | | |
| | Impact resistance toecap (clearance after impact 100J) | mm | N/A | N/A |
| | Compression resistance toecap (clearance after compression 10kN) | mm | N/A | N/A |
| | Impact resistance toecap (clearance after impact 200J) | mm | 15.0 | ≥ 14 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | 19.0 | ≥ 14 |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.