



Light

## CORTADO SB

Fashionable safety clog with backstrap

Safety Jogger's CORTADO is a stylish safety clog with antistatic, oil and fuel-resistant properties and is equipped with a backstrap. It offers superior heel energy absorption, breathability, and SR slip resistance.

Upper	Nappa Action Leather
Lining	Mesh
Footbed	SJ foam footbed
Midsole	N/A
Outsole	PU/PU
Toecap	Steel
Category	SB / SR, A, E, FO
Size range	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310
Sample weight	0.510 kg
Norms	ASTM F2413:2018 EN ISO 20345:2022



WHT




### Steel toecap

Robust metal support to protect the feet of the wearer against falling or rolling objects.



### SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



### Oil & fuel resistant

The outsole is resistant against oil and fuel.



### Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



### Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



### Antistatic

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm

**Industries:**

Catering, Chemical, Food &amp; beverages, Medical

**Environments:**

Dry environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
<b>Upper</b>	<b>Nappa Action Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	5.1	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	46	≥ 15
<b>Lining</b>	<b>Mesh</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	28.9	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	231.1	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
<b>Outsole</b>	<b>PU/PU</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	51.7	≤ 150
	Outsole slip resistance SRA: heel	friction	0.31	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.32	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.16	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	N/A	≥ 20
<b>Toecap</b>	<b>Steel</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	17.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	19.5	≥ 14

Sample size: 41

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.