



Light

DOLCE S3

Fashionable safety shoe, designed for the food industry

Safety Jogger's DOLCE is a multi-industry safety shoe featuring HACCP compliance, slip resistance, antistatic properties and more. It offers comfort, safety, and durability in demanding work environments.

| | |
|---------------|---|
| Upper | Nappa Action Leather |
| Lining | Mesh |
| Footbed | SJ foam footbed |
| Midsole | Steel |
| Outsole | PU/PU |
| Toecap | Steel |
| Category | S3 / SRC |
| Size range | EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310 |
| Sample weight | 0.625 kg |
| Norms | ASTM F2413:2018 EN ISO 20345:2011 |



217



S3
S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



SRA slip resistance
Slip resistance is one of the most important features of safety and occupational footwear. SRA slip resistant soles are tested on a ceramic tile with dilute soap solution.



Oil & fuel resistant
The outsole is resistant against oil and fuel.



Antistatic
Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



Water resistant Upper (WRU)
Prevents penetration of water if not permanently exposed to high levels.



Heel energy absorption
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

Industries:

Automotive, Catering, Construction, Food & beverages, Logistics, Industry

Environments:

Dry environment, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20345 |
|----------------|--|-----------------------|-------------|--------------|
| Upper | Nappa Action Leather | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 2.25 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 25 | ≥ 15 |
| Lining | Mesh | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 67.6 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 541 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | PU/PU | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 51.7 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.31 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.32 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.16 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.18 | ≥ 0.18 |
| | Antistatic value | MegaOhm | 120.1 | 0.1 - 1000 |
| | ESD value | MegaOhm | N/A | 0.1 - 100 |
| | Heel energy absorption | J | 29.2 | ≥ 20 |
| Toecap | Steel | | | |
| | Impact resistance toecap (clearance after impact 100J) | mm | N/A | N/A |
| | Compression resistance toecap (clearance after compression 10kN) | mm | N/A | N/A |
| | Impact resistance toecap (clearance after impact 200J) | mm | 15.5 | ≥ 14 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | 18.0 | ≥ 14 |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.