



**Heavy**

## PROMONORDI S3

Winterbox including the Nordic safety boot

Winterbox including 1 pair of Nordic safety boots, 1 pair of socks, 1 pair of winter working gloves and a warm Safety Jogger beanie

Upper	Corrected Nappa Leather
Lining	Teddy
Midsole	Anti-puncture Textile
Outsole	PU/TPU
Toecap	Composite
Category	S3 / SRC, CI
Size range	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 JPN 22.5-31 / KOR 235-310
Sample weight	0.825 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011




217



### Cold insulated (CI)

Cold insulated (CI) safety shoes keep your feet warm. They are worn in cold environments.



### Oil & fuel resistant

The outsole is resistant against oil and fuel.



### Water resistant Upper (WRU)

Prevents penetration of water if not permanently exposed to high levels.



### Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



### Composite toecap

Metalfree and lightweight, no thermal or electrical conductivity

**Industries:**

Automotive, Chemical, Cleaning, Construction, Logistics, Mining, Oil &amp; Gas, Industry

**Environments:**

Cold environment, Dry environment, Muddy environment, Snowy and icy, Uneven surfaces, Wet environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
<b>Upper</b>	<b>Corrected Nappa Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	2.6	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	25.8	≥ 15
<b>Lining</b>	<b>Teddy</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	34.5	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	276.9	≥ 20
<b>Outsole</b>	<b>PU/TPU</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	67.4	≤ 150
	Outsole slip resistance SRA: heel	friction	0.38	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.37	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.15	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.19	≥ 0.18
	Antistatic value	MegaOhm	65.7	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	33	≥ 20
<b>Toecap</b>	<b>Composite</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	16.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	17.5	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.